

INSTANT SURFACE RENOVATION

Innovation Competition BATIMAT 2009

DESTRUCTOR

PROPERTIES

DESTRUCTOR is a concentration of **high-power active substances** for instant **cleaning of all building surfaces** (floor, tiles, asbestos cement, stone, renderings, wood,...)

DESTRUCTOR cleanses the surfaces contaminated by **all sorts of mosses**, lichens, moulds, fungi, **pollution**, ... and is highly effective against **red stains** commonly seen on facade renderings.

Since **DESTRUCTOR** acts instantly, it takes **less than an hour** for all surfaces to regain their original aspect **without any alteration** of their mechanical properties.

DESTRUCTOR can be used as **a preventive** treatment before painting.

DESTRUCTOR eliminates the **bacteria** causing **stone crumbling** and **breaking down** (stone leprosis).

DESTRUCTOR is also the best product to renovate grey-tinted wood.

INSTRUCTIONS FOR USE

Dampen the surface with water and apply **DESTRUCTOR** pure or with a 50 % dilution.

Allow 20 to 45 minutes depending on the level of contamination and **rinse thoroughly** with a hose or a high-pressure cleaner.

<u>Caution</u>: **DESTRUCTOR's high detergent properties** may alter delicate materials or discolour concrete tiles and fake slates.

Always test beforehand.

Consumption:

1 litre for 3 to 6 m² according to soiling.

<u>Important</u>: **DESTRUCTOR** degrades when exposed to heat or UV.

Must be kept in the dark and at temperatures below 30 $^{\circ}$ C.

Never store in other container than the original one equipped with a degassing valve.

SAFETY PRECAUTIONS

Contains sodium hypochlorite, active CL solution (7%)

R31: Emits toxic gas when in contact with acid.

R34 : Causes burns.

S26: In case of contact with eyes, rinse thoroughly with water and see a doctor

S36/37/39: Wear adequate protective clothes, gloves, goggles and a face mask.

S45: In case of accident or discomfort, see a doctor immediately and show him/her the product label.

For professional use only.

Safety Sheet available on our Internet website www.perimetre-sa.com, "Product" section». Mentions responsabilité.

This technical sheet cancels and replaces all previous ones about this product.

The information provided on this technical sheet is based on our knowledge and the results of tests carried out with a concern for objectivity. They do not constitute a warranty on our part, or engage our liability with respect to the use of our products. It is the user's responsibility to test the products beforehand to make sure they are adapted to the task or material. Our warranty in respect to claims is limited to the replacement of defective product within a year after delivery.