



PERIMETRE

# ALL PURPOSE STRIPPER

## DKP 16

### PROPERTIES

All surfaces can be **stripped** by **DKP 16**.  
It can be used to **clean the surface** of all types of fouling.

**DKP 16** can be used :

- **For cement removal** on metallic surfaces ( wheelbarrows, concrete mixers, tools,...) and on **trims**.
- **For floor tiles stripping**, once laid, to eliminate the blush on terra cotta, floor tiles, sandstone , etc.....
- **For floor stripping** before screeds are laid.
- For moss and various fungi **removal on stones and coatings**.
- **To eliminate rust stains** on all surfaces.
- **To etch cement soils** and make them rough.
- **To eliminate wood tannins**
- **To eradicate efflorescences** that may appear when monolayer renderings dry up.

### INSTRUCTIONS FOR USE

**DKP 16** can be applied with a brush or sprayed.  
When stripping is **extremely difficult**, we recommend using it pure.  
In most cases, **DKP 16 is used diluted in water**.  
Dilution depends on the importance of the stripping or removal to be done.

*For example :*

- Removing **cement** on material : **DKP 16 PURE**
  - **Floor tiling** stripping : 1 L of **DKP 16** for 5 to 6 L of water
  - **Rendering** stripping : 1 L of **DKP 16** for 3 L of water.
  - **Efflorescence** eradication : 1 L of **DKP 16** for 10 L of water
- After each application, **rinse thoroughly in fresh water** to neutralise the product's effect.

**IMPORTANT** : On facade renderings and natural stones, damp the surface before applying **DKP 16**.  
Do not leave the product in contact with the surface for too long, rinse thoroughly afterwards with large quantities of water.  
Check the sensitivity of the surface to be treated beforehand since **DKP 16** is an aggressive product.

### SAFETY PRECAUTIONS

**DKP 16** contains hydrochloride acid : 32/33 % (hydrogen chloride solution).  
R35 : Causes severe burns.  
R37 : Irritant for airways.  
S1/2 :Keep locked away from children .  
S26 :In case of contact with eyes, rinse thoroughly with water and see a doctor.  
S45 :In case of accident or discomfort, see a doctor and show him/her the present sheet.  
Never use pure indoor.

*For professional use only. Risk of dangerous chemical reaction.  
Avoid contact or mixing with other chemical products ( chlorine included).  
Fiche de Sécurité sur Minitel au 08 36 05 10 12.*

**Cette fiche technique annule et remplace toutes les précédentes concernant ce produit. (Octobre 2000)**

Les informations contenues dans la présente notice sont l'expression de nos connaissances et des résultats d'essais effectués dans un souci constant d'objectivité. Elles ne peuvent cependant en aucun cas être considérées comme apportant une garantie ni comme engageant notre responsabilité en cas d'application défectueuse, puisque la manipulation et la mise en œuvre de notre produit échappe à notre contrôle. Il appartient à l'utilisateur de s'assurer par des essais préalables que le produit convient parfaitement à l'usage auquel il le destine. Notre garantie ne saurait excéder le remplacement d'un produit reconnu défectueux dans un délai d'une année après sa livraison

18/07/07