

# HYDRO M23

## PROPERTIES

**HYDRO M23** is a **colourless water repellent** product for new and old surfaces that doesn't alter the original aspect. (DTU 59.1.\*)

**HYDRO M23's new formula** now allows treatment on **dry or damp surfaces**.

This specificity allows a considerable **reduction of treatment costs** for very porous surfaces that can be **damped beforehand** to prevent the treatment from being absorbed too deeply.

**HYDRO M23** is **microporous** therefore it **lets the surface breathe** and allows **damp walls to dry up**.

Despite the **absence of film or thin skin**, **HYDRO M23** has a radical water repelling effect on the surface to be treated ( most coatings, stone, tiles, slates ) offering thereby both an **efficient anti-fouling** action and a **weathering protection** against extreme temperature variations.

**HYDRO M23** is **ideal for seepage problems** on roofs, facades, chimneys, caused by **microcracks or porous materials**.

**HYDRO M23 resin concentration** is far superior to that of most water repellents' on the market which makes it one of the **longest-lasting products**.

## 10 YEAR WARRANTY

*For professional use only. Risk of dangerous chemical reaction.*

*Avoid contact or mixing with other chemical products.*

*Fiche de Sécurité sur Minitel au 08 36 05 10 12.*

**Cette fiche technique annule et remplace toutes les précédentes concernant ce produit.(Octobre 2000)**

Les informations contenues dans la présente notice sont l'expression de nos connaissances et des résultats d'essais effectués dans un souci constant d'objectivité. Elles ne peuvent cependant en aucun cas être considérées comme apportant une garantie ni comme engageant notre responsabilité en cas d'application défectueuse, puisque la manipulation et la mise en œuvre de notre produit échappe à notre contrôle. Il appartient à l'utilisateur de s'assurer par des essais préalables que le produit convient parfaitement à l'usage auquel il le destine. Notre garantie ne saurait excéder le remplacement d'un produit reconnu défectueux dans un délai d'une année après sa livraison.

18/07/07

## INSTRUCTIONS FOR USE

Spray or brush **from bottom to top** until the surface is saturated.

**CONSUMPTION** : **1 L** of **HYDRO M23** to treat **3 to 5 M<sup>2</sup>** according to the material's porosity Very porous surfaces such as soft stone, raked plaster, can absorb up to **1 L** per **M<sup>2</sup>**. **Damping the surface** to be treated **beforehand**, without saturating it with water, will help reduce consumption.

**PRECAUTION** : The product is **rain resistant** 12 hours after application.

**HYDRO M23's** efficiency would be deeply altered if applied on surfaces cleaned with a chlorinated product.

For further information refer to data sheet CSTB N° 2843.

- NF P standard 74-201-1 (Oct 94)\*

Surface coatings and water repellent coatings belong to the "assimilated class" products and are classified as painting products according to the NF T 36-005 standard.

## SAFETY PRECAUTIONS

R10 : Flammable.

R65 : Noxious – Can be harmful for lungs if ingested.

R66 : Repeated exposure can cause skin fissures and desiccation.

S2 : Keep locked away from children

S16 : Keep away from ignition source. Do not smoke

S23 : Do not inhale gases, vapours, smokes.

S24/25 : Avoid contact with skin and eyes.

S43 : In case of fire, use CO<sub>2</sub>, dry powder or foam. Never use water.

S62 : If ingested, do not throw out, see a doctor immediately and show him/her the present specification sheet.