

SPEC'N SEL

PROPERTIES

SPEC'N SEL is made from the **best acrylic resins available on the market** and carefully calibrated silica.

SPEC'N SEL is the **only product** on the market combining the features of water-proofing systems used under floor tiles (SPEC) and liquid water-proofing systems (SEL).

SPEC'N SEL guarantees **perfect water-proofing under floor tiling or wall tiling** (according to DTU 52-1) both **vertically** and **horizontally**, and can be used **on all surfaces** (concrete, cellular concrete, plaster, gypsum board, tiling, wood, earthenware, aluminum, zinc...)

SPEC'N SEL is the best product to ensure **perfect water-proofing under floor tiling** for Italian showers, bathrooms, terraced roofs, balconies, basins, swimming pools, plant growers, etc...

SPEC'N SEL's properties allow the use of **non water-resistant plaster boards** in damp atmosphere. SPEC'N SEL's silicious structure **significantly enhances the adhesive properties** of tiling adhesives.

INSTRUCTIONS FOR USE

SPEC'N SEL can be applied either with a roller or a brush in two thin layers. The thickness of the final coating must be at least **0,4 mm**.

Make sure to **put enough product in corners, though avoiding overthickness**. SPEC'N SEL **must be covered**.

10 YEAR WARRANTY

Safety Sheet available on our Internet website www.perimetre-sa.com, "Product" section».

Mentions responsabilité.

This technical sheet cancels and replaces all previous ones about this product.

The information provided on this technical sheet is based on our knowledge and the results of tests carried out with a concern for objectivity. They do not constitute a warranty on our part, or engage our liability with respect to the use of our products. It is the user's responsibility to test the products beforehand to make sure they are adapted to the task or material. Our warranty in respect to claims is limited to the replacement of defective product within a year after delivery.

Since SPEC'N SEL remains soft when dry, cover strips in the corners are optional.

There is no need for primer due to SPEC'N SEL's **high resin content**.

Preparation of surfaces :

Moisten slightly to make sure surfaces are dust-free, especially joining strips and around them as well as old and porous materials.

Drying : allow **20 to 30 mn** between two layers and **30 mn before placing floor tiling**.

Temperature of surface and atmosphere:
+5 to + 30°C

Consumption : 5 m² per kg and 2 to 4.5 m² per kg on rough surfaces.

IMPORTANT :

Never apply SPEC'N SEL on a frozen surface nor in freeze-prone conditions within 24 hours.

Do not apply SPEC'N SEL when temperatures are too high, in full sun conditions or with a desiccating wind.

Rinse the material thoroughly with water before drying.

SAFETY PRECAUTIONS

Keep away from freeze and heat.

Close lid tightly after use.

R22 : Toxic if ingested.

R36 : irritant for the eyes.

R48/20 : **Toxic : risk of serious damage to health by prolonged exposure to inhalation.**