

TARDEX

DOSE

PROPERTIES

TARDEX is a **liquid admixture** used a **retarder for concrete and mortar.**

TARDEX has a **plasticizing effect** which can reduce water mixing quantity by 10%.

TARDEX **doesn't alter final mechanical resistance properties..**

When applied in warm conditions, **TARDEX** **prevents** screeds and coatings **from dessicating** too fast , thus turning powdery.

TARDEX is particularly suitable for the following cases :

All season screeds :

TARDEX's **retarding effect** is ideal for screed processing (DTU 26.2*). Since the mortar remains fresh longer, **floating operations are made far easier.**

Summer season shotcreting:

Tardex **makes coatings easier** even under warm weather conditions, because it allows a longer

time lapse between application and coating finishing..

Winter season shotcreting :

TARDEX **allows work** on the coating as early as application day + 1.

TARDEX can be used for all cement and lime mortars (DTU 26.1**). Besides, **TARDEX** is perfectly **compatible** with ready-to-use coating mixes.

INSTRUCTIONS FOR USE

Use one dose of TARDEX per sack of cement or for 6 ready-to-use coating mix sacks.

For further information refer to data sheet:

- NF standard P 14-201-1 (May 93)*
- NF standard P 15-201-1 (May 90)**

SAFETY PRECAUTIONS

Keep away from children.

For professional use only.

Fiche de Sécurité sur Minitel au 08 36 05 10 12.

Cette fiche technique annule et remplace toutes les précédentes concernant ce produit .(Octobre 2000)

Les informations contenues dans la présente notice sont l'expression de nos connaissances et des résultats d'essais effectués dans un souci constant d'objectivité. Elles ne peuvent cependant en aucun cas être considérées comme apportant une garantie ni comme engageant notre responsabilité en cas d'application défectueuse, puisque la manipulation et la mise en œuvre de notre produit échappe à notre contrôle. Il appartient à l'utilisateur de s'assurer par des essais préalables que le produit convient parfaitement à l'usage auquel il le destine. Notre garantie ne saurait excéder le remplacement d'un produit reconnu défectueux dans un délai d'une année après sa livraison.

18/07/07